



403

MAGNA 403 Hardfacing Electrode for High-Stress Abrasion

MAGNA 403



Hardfacing Electrode for High- Stress Abrasion

- *Work hardening austenite matrix with hard carbides – gives super abrasion resistance.*
- *Easy application – without spatter or pin holes.*
- *Can outwear ordinary hardfacing rods 8-to-1.*

TRUST *Ease of Application*
MAGNA *Wide Versatility*
FOR *Outstanding Physical Properties*



SPECIAL FEATURES

Magna 403 Hardfacing Electrode for High-Stress Abrasion is the "Problem Solver" electrode.

- **Magna 403** features a dense work-hardening austenite matrix with hard carbides to resist both high-stress and low-stress abrasion.
- **Magna 403** provides easy application without spatter or pin holes – ensures easy slag removal.
- **Magna 403** outwears ordinary hardfacing rods by as much as 8-to-1.

OUTSTANDING PROPERTIES

Magna 403 is the hardfacing electrode for high-stress abrasion that:

- Withstands high-friction temperatures, yet will not crack at low temperatures
- Is highly alloyed so that hardness is not dependent on cooling rate.
- Provides a high deposition rate.
- Gives smooth, neat deposits.
- Provides hardness of 55 to 60 Rockwell C as applied.

USE FOR

Magna 403 (for AC & DC) is the right choice for hardfacing welds that must withstand all types of high-stress abrasion, including erosion, scratching, grinding and gouging.



ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Magna Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.



The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016